



Sanitary inner "deep-drawn" wash tank

### CONSTRUCTION FEATURES

- Body, external housing, wash tank, and all chassis components in brushed stainless steel AISI 304 18/10
- Noise 58 DbA due to utilization of double-wall insulated panels
- Upper and lower wash and rinse jets on revolving arms constructed of fiberglass; easy to remove and clean without the need for tools
- Integrated AISI 304 18/10 stainless steel booster
- Safety micro-switch on the door to interrupt wash pump action
- Independently-operated heating elements alternating between booster and wash tank
- Alternating heating resistors reducing maximum absorption thereby reducing energy costs
- Possibility of built-in or free-standing installation
- Standard equipment includes insulated top and side panels
- Deep drawn inner chamber constructed without welds or corners
- Wash tank protected with double filters, plus additional filter for overflow tube
- Door-opening with overall clearance of 12 in. (30 cm)
- Automatic fill and water level regulation of tank
- Slide out integrated front control panel with easy access for service
- Individual digital thermometer gauges displaying wash and rinse temperatures
- Standard equipment includes: One 16- compartment (4x4) angled section glassware rack and one open combination rack for cups, bowls, and assorted wares



### JET TECH SYSTEMS CORP.

TEL: (514) 737-9701 FAX: (514) 342-3854  
 TOLL FREE: (888) ASK 4 JET  
 jet-tech.com sales@jet-tech.com

In line with our continuing policy on research and product development, we reserve the right to alter specifications without notice.



Slide out integrated control panel

### TECHNICAL FEATURES

- **Rack capacity:** 15.75" x 15.75" (400 mm x 400 mm)
- **Complete cycle:** 120 seconds (105 sec. wash & 15 sec. rinse)
- **Wash tank capacity:** 2.12 U.S. gallons (8 liters)
- **Wash tank element:** 2000 Watts
- **Wash temperature:** 150°F. (65°C.)
- **Booster capacity:** 1.27 U.S. gallons (4.8 liters)
- **Booster element:** 2400 Watts
- **Booster (water) temperature:** 185°F. - 194°F. (85°C. - 90°C.)
- **Power supply:** single-phase 208-240 V. 60 Hz. 14.1 Amps
- **Motor-pump:** 0.75 H.P. with clipson at 320F. (160C.)
- **Maximum power rating:** 3000 Watts
- **Water consumption per cycle:** 0.66 U.S. gallon (2.5 liters)
- **Flow pressure:** 25 p.s.i. (optimum)
- **Water inlet connection:** 3/4" male garden hose fitting (hose not included)
- **Drain connection:** 1" ID hose connection (hose not included)
- **Shipping weight:** 116 lbs. (53 kg.)

