

model 737



Undercounter “Deluxe” Dishwasher

**Fully automatic program with wash phase at 150°F (65°C.)
and final rinse phase at 185°F. (85°C.)**


Capacity: 30 racks per hour

Sanitary labyrinth door eliminates need for gasket

Built-in rinse-additive pump for sparkling results

Built-in automatic detergent pump for consistent results

Built-in automatic drain pump for ease of installation



Sanitary inner "deep-drawn" wash tank

CONSTRUCTION FEATURES

- Body, external housing, wash tank, and all chassis components in brushed stainless steel AISI 304 18/8
- Noise 58 DbA due to utilization of double-wall insulated panels
- Upper and lower wash and rinse jets on revolving arms constructed of fiberglass; easy to remove and clean without the need for tools
- Integrated AISI 304 18/10 stainless steel booster with insulated lining
- Safety micro-switch on the door to interrupt wash pump action
- Independently-operated heating elements alternating between booster and wash tank
- Alternating heating resistors reducing maximum absorption thereby reducing energy costs
- Possibility of built-in or free-standing installation
- Standard equipment includes both sides and top panels that are easily removed
- Deep drawn inner chamber constructed without welds or corners and recessed wash tank make the 737 ideally suited for Marine usage
- Wash tank protected with double filters, plus additional filter for overflow tube
- Door-opening with overall clearance of 14.25 in. (36 cm)
- Automatic fill and water level regulation of tank
- Upper removable integrated front control panel with easy access for technical maintenance
- Individual digital thermometer gauges displaying wash and rinse temperatures representing high technology
- Overall dimensions: Height: 33.5 in. (850 mm)
Width: 23.75 in. (600 mm) Depth: 23.75 in. (600 mm)



JET TECH SYSTEMS CORP.

TEL: (514) 737-9701 FAX: (514) 342-3854
TOLL FREE: (888) ASK 4 JET
jet-tech.com sales@jet-tech.com

In line with our continuing policy on research and product development, we reserve the right to alter specifications without notice.



Removable integrated control panel

TECHNICAL FEATURES

- **Rack capacity:** 19.75" x 19.75" (500 mm x 500 mm)
(One open combination rack and one peg dish rack supplied)
- **Complete cycle:** 120 seconds (105 sec. wash & 15 sec. rinse)
- **Wash tank capacity:** 3.17 U.S. gallons (12 liters)
- **Wash tank element:** 2800 Watts
- **Wash temperature:** 150°F. (65°C.)
- **Booster capacity:** 1.72 U.S. gallons (6.5 liters)
- **Booster element:** 4000 Watts
- **Booster (water) temperature:** 185°F. - 194°F. (85°C. - 90°C.)
- **Power supply:** single-phase 208-220 V. 60 Hz. 22 Amps
- **Motor-pump:** 0.75 H.P. with clipson at 320F. (160C.)
- **Maximum power rating:** 4550 Watts
- **Water consumption per cycle:** 0.79 U.S. gallon (3 liters)
- **Working pressure:** 25 p.s.i. (dynamic)
- **Water inlet connection:** 3/4" flexible garden-hose type
- **Weight:** 165 lbs. (75 kg.)

