



Drop in Gas Cooktops – Install Quick Specs CTG 36” Wide

Installation Type

Drop into countertop opening

Overall & Cutout Dimension(s)

CTG365D	A	B	C
Overall	36”	20 1/8”	2 29/32”
	D	E	
Cutout	35 3/8”	19 1/2”	

Standard Features

- 304 Series, 18 gauge stainless steel maintop and frame
- Five high output burners (Model: CTG365D)
- Individual burner electronic ignition and re-ignition system
- One-piece brass burner heads for durability and more precise flame control
- Low grate profile of only 3/4” above countertop
- Shallow rough-in box depth for extra cabinet storage
- Die cast, counter balanced control knobs

Finishes

- Stainless Steel (S)

Optional Upgrades

- Cast Wok Ring (Model: WOKRING)
- Liquid Propane (LP) models available

Gas Supply Requirements*

NG Standard: 1/2” regulator (6 to 14 inches water column/Manifold at 4-inches)

LP Standard: 1/2” regulator (11 to 14 inches water column/Manifold at 10-inches)

*Regulator ships in box with cooktop. LP gas tank must have its own pressure regulator in addition to the one provided with the cooktop

Maximum Power Supply Required

15 amps @ 120 V AC, 60 Hz, single phase
Cooktop comes with a 4’ long grounded cord.

A three-prong ground receptacle is required. Gas supply and electric are located off the right rear of the cooktop

Cooktop Carton Weight:

CTG365D = 83 lbs.

