



Sushi

Counter top stainless steel
refrigerated display case

KSDC SERIES

| | |
|---------------|-------|
| Project name: | |
| Location: | |
| Item: | Qty : |
| Model: | |

KSDC SERIES



Features

- Designed to display sushi, meats, salads, desserts and many other items for quick point of purchase sales
- Curved front tempered glass for added visibility, safety and increased durability
 - Hinged front glass tilts forward to simplify cleaning
- Interior LED lighting (with protective cover) enhances overall product appearance
 - Removable sliding rear doors allow for easy access and simplify cleaning
- Upper double evaporator fin-type coil assures proper temperature throughout the cabinet
 - Electronic thermostat maintains temperatures between 33°F/1°C and 40°F/7°C, digitally displays temperature at all times
- Upper stainless steel baffle plate creates a drip-free food safe environment
 - Available with either a left side or right side compressor
 - Sealed compressor with a double-vented high quality condenser
 - 304 finish stainless steel deep drawn inner pan
 - Automatic defrosting
 - Stainless steel body
- Condensate from upper coil drains directly into a shelf contained evaporation channel, eliminating any drain connection requirement
 - Environmentally friendly R134-A type Freon
- These units are designed for maximum performance in an air-conditioned area of 77°F ambient temperature and 55% relative humidity



KSDC SERIES

| Model | Width | | Depth | | Height | | NET Weight | Max Capacity | SHIPPING SPECS | | | |
|-----------------|-------|-------|-------|-------|--------|------|------------|--------------|----------------|-------|--------|---------|
| | Ext. | Int. | Ext. | Int. | Ext. | Int. | | | Weight | Depth | Height | Weight |
| KSDC - 5 | 65.5" | 41.3" | 15.1" | 12.1" | 12.0" | 6.2" | 101 lbs | 2.88 cu.ft | 65.5" | 23.2" | 22.5" | 145 lbs |
| KSDC - 6 | 70.4" | 55.0" | 15.1" | 12.1" | 12.0" | 6.2" | 114 lbs | 3.83 cu.ft | 79.2" | 23.2" | 22.5" | 170 lbs |
| KSDC - 7 | 84.3" | 70.0" | 15.1" | 12.1" | 12.0" | 6.2" | 123 lbs | 4.80 cu.ft | 91.3" | 23.2" | 22.5" | 190 lbs |

| | | | |
|-------------------------------|-----------|--------------------------|--------------------|
| Electrical : | 115/60/1 | Saturation temperature : | 33°F/1°C |
| Voltage variation : | + / - 10% | Ambient temp : | 77°F/25°C, no load |
| Rated amperage : | 4.5 A | Refrigerant type : | R-134A |
| Maximum ambient temperature : | 77°F/25°C | Maximum load height : | 5.4" |
| Compressor : | 0.25 HP | | |

These units are designed for maximum performance in an air-conditioned area of 77°F ambient temperature and 55% relative humidity. There must be adequate ventilation at the top, sides & rear of the unit for proper operation.

Important : this unit doesn't have an automatic defrost system and must be turned off at night to allow the evaporator to defrost

Warranty : 12 months parts & labor, 24 months on the condenser & compressor



KOOL-IT is a registered trade mark of MVP Group.
Specifications subject to change without notice.