



W30A Food Mixer - 30 Quart Mixer

Project _____

Item Number _____

Quantity _____



Variable speed V-belt transmission based on precision machined cast iron pulleys.

Welded stainless sheet metal construction for strength and rigidity.



ETL listed
Conforms to UL Std 763
Certified to CSA Std C22.2 No.195



Standard Features

- Powerful 2 hp motor
- Variable Speed Drive with wide agitator speed range from 60 rpm to 300 rpm
- #12 attachment hub with 198 rpm speed
- Top cover, planetary cover and bayonet shaft in stainless steel. Durable powder coated finish used on outside surfaces not constructed of stainless steel.
- Rubber feet.
- Stainless Steel safety guard
- Front mounted controls with 15-minute timer with HOLD feature
- No bowl adaptors required for the down-size bowls
- By manually operating a single lever, the bowl raises and locks in position. Bowl lowering made easier by hydraulic damper
- High torque transmission. Grease lubricated, anti friction ball bearings.
- Permanently lubricated planetary head and attachment hub case
- Locking pin on tools instead of shaft.
- Safety cut-switch automatically turns the mixer off if safety guard is open or bowl is lowered.
- Overload protection and no voltage release
- 6 feet cord
- ETL and NSF listed

Optional Features

- Mixer in Stainless Steel
- Marine version USPHS
- Prison package
- Mark IV Control System

Standard Accessories:

- 32 quart bowl - Stainless steel
- Flat beater - Stainless steel
- Wire whip - stainless steel wires
- Dough hook - stainless steel

Optional Accessories:

- 16 quart bowl and accessories
- Bowl scraper in 32 quart and 16 quart sizes
- Stainless steel wing whip
- Heavy wire whip
- Bowl truck
- Stainless steel splash guard
- Bowl guard ingredient chute

Optional Attachments:

- Food slicer
- Meat grinder

Optional Equipment:

- Bowl lift Easylift II

Warranty:

One year parts and labor limited warranty

Approved By: _____



Date: _____

 **Varimixer**
www.varimixer.com

14240 South Lakes Drive
Charlotte, NC 28273
Phone: 800-222-1138
Fax: 704-583-1703
mixer@varimixer.com



W30A Food Mixer - 30 Quart Mixer



**Bowl lift
Easylift II**



Bowl scraper



Bowl truck



**Food slicer
312GS**



**Meat grinder
302**

Specifications

Model No.	Capacity	Overall size			Net. weight
	Large bowl 32-qt. Small bowl 16-qt.	Height H	Width W	Length L	
W30A		47.625" (120.97 cm)	21" (53.34 cm)	35.81" (90.96 cm)	456 lbs. (206.84 kg)

Shipping information

Class	CU. FT.	Dimensions			Weight
		Height	Width	Length	
85	55	61" (154.94 cm)	32" (81.28 cm)	49" (124.4 cm)	525 lbs. (238.14 kg)

Cord & Plug

Attached 6 foot flexible 3-wire cord

Electrical Data for Motor

Motor	Volts	Amp
Standard	2 HP 115/60/1	20
Optional	2 HP 208/60/1	10
Optional	2 HP 208/60/3	6.4
Optional	2 HP 480/60/3	4.4

On the nominal motor voltage, + or - 10% tolerance is allowed.

Mixing Speed

Agitator Speed	Min	Max	Hub
	60	300	198

Mixer in Stainless Steel

Marine version USPHS: Stainless steel execution, stainless steel bowl arms, water cover at air ventilation, slotted free screws, full welded stainless steel knees.

Prison package

MK IV Control Panel: Programmable electronic panel

Capacity Chart

Mashed Potatoes	Whip or Beater.....	26 lbs.
Whipped Cream	Whip.....	6 Qts.
Muffins.....	Beater	35 lbs.
Layer Cake	Beater	35 lbs.
Pancake Batter.....	Whip or Beater.....	14 Qts
Cookie Dough.....	Beater or Hook.....	20 lbs.
Donuts, Yeast	Hook	34 lbs.
Donuts, Cake.....	Beater	34 lbs.
Bread Dough (65% AR).....	Hook	35 lbs.
Pizza Dough (50% AR).....	Hook	25 lbs.

%AR= $\frac{\text{weight of water}}{\text{weight of flour}}$

Batch size and/or speed reduction is required if any of the following conditions exist.

1. High Gluten Flour
2. AR % under 40%
3. Water Temperature under 65 Degrees F.



Varimixer

www.varimixer.com

14240 South Lakes Drive

Charlotte, NC 28273

Phone: 800-222-1138

Fax: 704-583-1703

mixer@varimixer.com