





G14 Medium Duty Manual Slicer

Globe Models

☐ G14 - 14" Diameter Knife Manual Slicer

Standard Features

- 14" knife, special alloy hollow ground and hard chromed
- Powerful ½ HP knife motors
- Motor overload protection with manual reset

G14

- Top mounted all metal knife sharpener
- 0 to 9/16" slice thickness
- Anodized aluminum construction with seamless edges and radius corners
- · Oversized positive traction grooved belt drive
- Knife cover interlock
- Large product receiving area
- Smooth stainless steel ball bearing chute slide
- 35° angled food chute
- Dual purpose handle with improved ergonomic design
- Power indicator light
- Removable, easy-to-clean chute, slice deflector, knife cover and sharpener
- Metal bottom enclosure
- Permanently attached knife ring guard
- · No voltage release relay system





Optional Accessories

- ☐ G14 Slicer Cover SC-LARGE
- ☐ G14 Food Fence M500A - (10 5/8" L x 1 3/8" H)

Standard Warranty

Approved By:_____

Date:__

One-year parts and labor

Globe

GLOBE FOOD EQUIPMENT COMPANY

www.globeslicers.com

2153 Dryden Rd. **Y** Dayton, OH 45439

> Phone: 937-299-5493 Phone: 800-347-5423 Fax: 937-299-4147





Medium Duty Manual Slicer

Finish: Heavy gauge anodized aluminum that is stain resistant, long lasting and easy to clean.

Motor: Powerful motors, fan cooled, permanently lubricated ball bearings ensure quiet operation. Thermal overload protection included.

G14: ½ HP, 115-60-1, 3 amps

Manual Reset Button: Motor overload protection allows the operator to reset the slicer manually.

Knife Drive: Knife is driven by a positive grooved belt that works well in medium duty applications.

Slice Thickness: Food can be sliced from 0 to 9/16" thick.

Top Mounted Sharpener: Sharpener is all metal construction and is top mounted for easy access. A two stone, dual action design allows you to quickly return a razor sharp edge to your knife. Sharpener is removable for cleaning.

Hollow Ground Knife:

Hard chromed, special alloy hollow ground blade lasts longer and sharpens easily.

G14: Nominal 14" diameter

On/Off Controls: Separate on/off push button type.

Specifications

Ball Bearing Chute Slide

System: Ball bearing system ensures smooth and easy movement of the food chute assembly.

Knife Hub: Knife hub bearings, belt and motor are fully enclosed, protecting them from moisture.

Knife Cover Interlock: Slicer will not operate with the knife cover removed.

Knife Ring Guard: Permanently mounted knife ring guard protects the non-slicing portion of the knife. Slicer table protects leading edge of the knife when completely closed.

Table Rod: Separate table support rod is protected by the table casting and cover.

Bottom Enclosure: Components are safeguarded by a cover protecting them from food and other debris.

No Volt Release Relay: Prevents inadvertent activation of the slicer in the event of power interruption.

Slice Deflector: Deflector is securely fastened to the slicer; simple to remove without tools and easy to clean.

Rubber Feet: Supplied with nonslip rubber feet.

Capacity:

Height 10.125" (25.7cm), Width 11.5" (29.2cm), Diameter 9.75" (24.8cm)

Cord & Plug: Attached 6 foot flexible 3-wire cord and plug fits a grounded receptacle.

Dimensions (G14): Foot Print: 14"W x 21"D (35.6cm x 53.4cm)

Overall Length: 27.625" (70cm) Overall Width: 20" (51cm) Overall Height: 19.25" (49cm)

Freight Class: 85 Net Weight: 64lbs. (23kg) Shipping Weight: 125 lbs. (57 kg)

Box Dimensions: 24"W x 31.5"D x 31"H (61cm W x 80cm D x 79cm H)

Optional Accessories: M500A - Food fence (10 5/8" L x 1 1/6" H) SC-LARGE - Slicer Cover



GLOBE FOOD EQUIPMENT COMPANY

www.globeslicers.com

2153 Dryden Rd. Dayton, OH 45439 Phone: 937-299-5493 Phone: 800-347-5423 Fax: 937-299-4147