



Assembly Time


equal assembly time



equal assembly time

Posts

1" diameter adjustable on 1" increments numbered on 1" increments



1" diameter adjustable on 1" increments numbered on 2" increments

Leveling Bolt



domed shoulder does not collect dirt



domed shoulder does not collect dirt

Sleeve



two piece plastic split sleeve



two piece plastic split sleeve

Shelf Collar



tapered collar snugly locks on tapered plastic split sleeve



tapered collar snugly locks on tapered plastic split sleeve

Mat Wires


#9 wire (.1483 dia.) on .7917 centers, #6 wire (.1920 dia.) shelf support wires



#9 wire (.1483 dia.) on .7917 centers, #6 wire (.19210 dia.) shelf support wires

Shelf Frame



1/4 rod (.250 dia.) on frame
1/4 rod acts as natural ledge to prevent items from falling off



1/4 rod (.250 dia.) on frame
1/4 rod acts as natural ledge to prevent items from falling off

Strength & Shelf Deflection

Equal deflection under load



Equal deflection under load

Standard Finishes

POLY-Z-BRITE, Chrome, NEXELON

Super Erector Brite, chrome, Metroseal II

Protective Coating Thickness

.0001 avg.

Chrome



Chrome



.0001 avg.