



Model AXP22T shown

15 times faster than conventional ovens.

Heavy Volume | Combination Cooking
This category of combination oven is ideal for...

Application:

- Theatres
- Convenience stores
- Satellite locations
- Healthcare
- Stadiums
- Pizzerias
- Hotel room service
- Campus dining
- Snack bars

Through put potential:

- 12" frozen pizza, 20 per hour
- 6" toasted sub sandwiches, 80+ per hour
- Grilled fresh salmon, 20 per hour
- Crème brulé, 10 per hour
- 1 lb. portions fresh shrimp, 30 portions per hour

Location of oven(s):

- Kitchen shelf
- Kitchen countertop, single or stacked
- Equipment stand, single or stacked

Defrost:

- Defrosts most frozen food products in microwave mode

All ACP, Inc. commercial ovens are backed by our Culinary Center. Call us with any question regarding food preparation, menu development and cooking times 866-426-2621.





High Speed Combination Oven

Amana® Commercial AXP22T

Power Output

- Forced convection:
 - 2000 W
 - 200° - 520° F (95° - 270° C) temperature range
 - Forced convected air for enhanced toasting and browning
- Microwave:
 - 2200 W
 - Heats quickly, reduces cooking time
- Infra-red radiant:
 - 3000 W
 - Enhances toasting and browning



Cuts Costs

- No need for costly ventilation hood - catalytic converter filters grease and odors from the air. Integrated recirculating catalytic converter.
- Uses less energy than a conventional oven.
- Eliminates need for pre-cooking and holding.
- Uses standard metal trays, pans and screens.

Simplifies Cooking

- Touch screen operation for consistent results.
- Transfer programming information via USB port, wi-fi or ethernet
- Controls are intuitive and simple to use.
- Stores up to 360 menu items.
- Four stage cooking option.
- 1.38 cubic ft. (39 liter) oven capacity.
- Door drops down below oven rack providing full access to oven interior.

Easy to Use and Maintain


- Porcelain IR element cover enhances operator safety and simplifies maintenance
- Stainless steel exterior and interior.
- Infra-red elements tilt-up for cleaning.
- Two removable air filters protect oven components.
- Backed by the ACP, Inc. 24/7 ComServ Support Center, 866-426-2621.
- ETL Listed.



Patents Pending



Amana® Commercial AXP22T | High Speed Combination Oven



Installation Clearances - Top: 2" (51), Sides: 1" (25), Back: None

Drawings available from KCL CADlog - techs@kclcad.com

Specification #:

Specifications			
Model	AXP22T	728028377118	
Cooking Power*	2000W	2200W	3000W
	Forced Convection	Microwave	Infra-red radiant
Configuration	Countertop		
Menu Capacity	360 items		
Power Levels	11		
Max. Cooking Time	60:00		
Program Menu	Multi-level menu capability		
Defrost	Yes, microwave only, power level 2		
Time Entry Option	Yes		
Microwave Distribution	Double side oscillating antenna		
Magnetrons	2		
Display	Touch screen, color LCD		
Stackable	Yes		
Stage Cooking	Yes, 4		
Door Opening	Pull down, ergonomic handle		
Automatic Voltage Sensor	Yes		
USB Port	Yes		
Temperature Range	200° - 520° F (95° - 270° C)		
Air Filter	2 removable, with clean filter reminder		
Fan Speed	0-100%		
Rack	1 rack position, removable		
Exterior Dimensions	H 20 3/8" (518)	W 25 1/8" (638)	D** 27 1/2" (699)
Cavity Dimensions	H 10" (254)	W 16" (406)	D 15" (381)
Door Depth	37 5/8" (956), drop down door		
Usable Cavity Space	1.38 cubic ft. (39 liter)		
Exterior Finish	Stainless steel		
Interior Finish	Stainless steel		
Power Consumption	5700 W, 27.4A		
Power Output*	2200 W* Microwave		
Power Source	208 - 240 V, 60 Hz, 30 A single phase		
Plug Configuration / Cord	NEMA 6-30	5 ft. (1.5 m)	
Frequency	2450 MHz		
Product Weight	150 lbs. (68 kg.)		
Ship weight (approx.)	175 lbs. (79 kg.)		
Shipping Carton Size	H 32 1/2" (826)	W 28 1/4" (717)	D 34 3/4" (883)

Specifications

Oven shall combine three cooking modes: forced convection, microwave and infra-red radiant for high speed cooking. Icon operated control panel shall be programmable with the ability to program a maximum of 360 menu items and shall have multi-level menu capability. Programs shall be automatically updated using either Wi-Fi, ethernet or USB port. Display shall be a swipe touch screen, color LCD. There shall be 11 power levels, 4 cooking stages and defrost mode. Microwave output shall be 2200 watts and distributed from two magnetrons located on each side of the cavity. An automatic voltage sensor shall accommodate either 208 or 240 volts with no manual adjustment. Oven shall provide a temperature range from 200° - 520° F (95° - 270° C) in 5° increments. The convection fan shall distribute the heat throughout the cavity to further reduce cook times. Fan speed can be programmed from 0 to 100% for menu flexibility. The infra-red radiant shall have 3000 watt output and deliver heat from the bottom of the oven. This element shall be concealed with porcelain cover and hinged for easy cleaning of the oven floor. The oven cavity shall have a 1.38 cubic ft. (39 liter) capacity and use standard metal cookware. Maximum microwave cooking time shall be 60 minutes. Oven shall have a stainless steel exterior and be stackable. Oven cavity shall be stainless steel construction with stainless oven door. Drop down door shall open below oven rack for full access to the cavity. The two side air filters shall be removable for easy cleaning and have a "clean filter" reminder feature. A removable, one position rack shall be included. Microwave oven shall comply with standards set by the U.S Department of Health and Human Services, ETL listed for safety and sanitation.

Included Accessories:

- Oven paddle

Optional Accessories

- Panini press
- Pizza stone 14 3/8" (365mm) dia.
- Leg kit - set of four 4" (102mm) legs
- Non-stick baskets - set of two
 - 10" x 12" x 1" (254 x 305 x 25mm) size
 - 6" x 12" x 3/4" (152 x 305 x 19mm) size
- Stainless carts/equipment stands 24" (610) and 30" (762)

Warranty

Warranty Certificate for this product can be found on the ACP, Inc. website at: www.acpsolutions.com/warranty

Service

All products are backed by the ACP, Inc. 24/7 ComServ Support Center.



AIA File #:

Measurements in () are millimeters

* IEC 60705 Tested

** Includes handle